

Inserta Products, Inc.

MODULAR CONNECTORS

MODULAR CONNECTORS UNIFIED CODE U61 2-BOLT FLANGE TYPE

INSERTA® UNIFIED CODE U61 2-Bolt Modular Connectors are used in integrated hydraulic systems in place of welded and threaded pipe fittings. These 2-Bolt Modular Connectors offer great flexibility and additional options for making compact integrated hydraulic system. The 2-Bolt Modular Connectors should be used whenever the features of the 4-Bolt design are not required.

INSERTA® UNIFIED CODE U61 2-Bolt Modular Connectors use the upper right and lower left threaded holes of the **INSERTA® UNIFIED CODE U61 4-Bolt** port pattern for the **2-Bolt** connections.

Design-A and Design-B Modular Connector elbows, run tees, branch tees, crosses, and port spacers are held in place by bolts (Socket Head Cap Screws) that extend from Face 1 to Face Ø in the 2-bolt flange pattern.

Design-A incorporates the 2-bolt clamp face groove and sealing O-ring on Face Ø and a plain face on Face 1. This design permits the stacking of various **INSERTA®** inline modules together with a minimum of O-ring seals to virtually eliminate leaks associated with pipe threads. The task is further enhanced because large wrenches with high torque normally needed to install pipe fittings are no longer necessary since the components bolt together.


Design-B eliminates the 2-bolt clamp face groove and O-ring on Face Ø for those applications that require this geometry.

Design-C eliminates the Face 1 to Ø thru hole characteristics of Designs A & B. Design-C has port faces on all designated faces, and therefore are not held together by thru bolts, but are port faces that other flange type components are fastened. The nesting of the 2-bolt mounting holes on adjacent port faces makes these Design-C 2-Bolt Modular Connectors more compact than the Design C 4-Bolt Modular Connectors.

INSERTA® UNIFIED CODE U61 2-Bolt Port Spacers should also be used between CODE 61 and CODE U61 4-Bolt Ports and the connected **ADAFLANGE™ UNIFIED CODE U61 2-BOLT Adapters** to cover and protect the two unused mounting holes.

The **INSERTA® UNIFIED CODE U61 2-Bolt Retainer Connector** uses the same two threaded holes to retain either 2 or 4-Bolt Flange Type modules, and has the bolt holes counter-bored to recess the heads of the Socket Head Cap Screws. These Retainer Connectors have the other two diagonal holes of the 4-Bolt Port pattern threaded for fastening an **ADAFLANGE™ UNIFIED CODE U61 2-Bolt Adapter**. This Retainer Connector feature is also available as a built in option in the **INSERTA® ICX and ITR Modular Connectors**.

Standard **INSERTA® Unified CODE U61 2-Bolt Modular Connectors** have all flange ports of the same size, and are made of steel.




ORDERING INFORMATION


UNIFIED WITH SAME SIZE OUTLETS

<p>INSERTA®</p> <p>MODULAR CONNECTORS U61 2-BOLT TYPE</p> <p>CX = CROSS EL = ELBOW RC = RETAINING CROSS RT = RETAINING TEE RUN TR = TEE, RUN TB = TEE, BRANCH PS = PORT SPACER (A & B DESIGN) PN = PORT CONNECTOR (C DESIGN) PR = PORT RETAINER (A & B DESIGN)</p> <p>MOUNTING DESIGN CODE</p> <p>A = SEAL GROOVE & O-RING ON FACE Ø WITH 2-BOLT PATTERN THRU HOLES FROM FACE 1 TO FACE Ø B = PLAIN FACE Ø WITH 2-BOLT PATTERN THRU HOLES FROM FACE 1 TO FACE Ø C = 2-BOLT FLANGE PORTS ON ALL DESIGNATED FACES</p> <p>MOUNTING PATTERN U 261 = UNIFIED CODE U61 2-BOLT</p>	<p>ICX — A — U261 24 * — N — G* — T*</p>	<p>TEST PORT T = #4 SAE (7/16-20) or P=1/4 NPTF * = 1, 3, 4 and 5 PORT FACE POSITIONS (See Page 20 for Selection Availability)</p> <p>GAUGE PORT G = #6 SAE (9/16-18) * = 1, 3, 4 and 5 PORT FACE POSITIONS (See Page 20 for Selection Availability)</p> <p>SEAL COMPOUND (OMIT FOR DESIGNS B & C) N = BUNA N (STANDARD) V = VITON</p> <p>PORT SPACER/CONNECTOR h, DIMENSION (1/4 INCREMENTS) 1 = 1/4 THICK 2 = 1/2 THICK OMIT = The non 1/4 increment standard PS or PC</p>	<p>NOMINAL SIZE</p> <table border="0" style="width: 100%;"> <tr> <td>02 = 1/8</td> <td>16 = 1</td> </tr> <tr> <td>04 = 1/4</td> <td>20 = 1 1/4</td> </tr> <tr> <td>06 = 3/8</td> <td>24 = 1 1/2</td> </tr> <tr> <td>08 = 1/2</td> <td>32 = 2</td> </tr> <tr> <td>12 = 3/4</td> <td></td> </tr> </table>	02 = 1/8	16 = 1	04 = 1/4	20 = 1 1/4	06 = 3/8	24 = 1 1/2	08 = 1/2	32 = 2	12 = 3/4	
02 = 1/8	16 = 1												
04 = 1/4	20 = 1 1/4												
06 = 3/8	24 = 1 1/2												
08 = 1/2	32 = 2												
12 = 3/4													

Inserta Products, Inc.
Blue Bell, Pa. 19422


MODULAR CONNECTORS
UNIFIED CODE U61
2-BOLT FLANGE TYPE






DESIGN A = AS SHOWN on drawings above and the title block schematics below.
 DESIGN B = Eliminates seal groove and O-Ring from Face-Ø.
 *NOTE: Port Spacer available in 2 standard h₁ sizes.

NOMINAL PATTERN SIZE	H	L	W	X	K	h ₁			K	O-RING SIZE NO.	ELBOW CLAMP FACE BOLT KITS (2 BOLTS)	PR BOLT LENGTHS
					EL	PS*	PN	PR	PR			
U26102	.62	1.00	1.00	.31	.37	.12/.25	.34	.50	.31	010	IBK-SH2008-32x0.62	0.62
U26104	.75	1.25	1.12	.38	.50	.12/.25	.38	.50	.31	011	IBK-SH2010-24x0.87	0.62
U26106	.87	1.50	1.38	.44	.62	.12/.25	.50	.50	.25	014	IBK-SH2025-20x1.00	0.62
U26108	1.31	2.12	2.00	.66	1.00	.25/.50	.62	1.00	.69	210	IBK-SH2031-18x1.50	1.25
U26112	1.62	2.56	2.38	.81	1.12	.25/.50	.75	1.00	.62	214	IBK-SH2038-16x1.75	1.25
U26116	1.87	2.75	2.50	.94	1.38	.25/.50	.75	1.00	.62	219	IBK-SH2038-16x2.00	1.25
U26120	2.12	3.12	2.88	1.06	1.66	.25/.50	.88	1.00	.56	222	IBK-SH2044-14x2.50	1.25
U26124	2.50	3.69	3.38	1.25	1.94	.25/.50	1.00	1.00	.50	225	IBK-SH2050-13x2.75	1.25
U26132	3.00	4.00	3.75	1.50	2.44	.25/.50	1.00	1.00	.50	228	IBK-SH2050-13x3.25	1.25



Inserta Products, Inc. Blue Bell, Pa. 19422	MODULAR CONNECTORS UNIFIED CODE U61 2-BOLT FLANGE TYPE	 EL	 TR	 TB	 CX
		 EL	 TR	 TB	 CX




DESIGN A = AS SHOWN on drawings above and the title block schematics below.
 DESIGN B = Eliminates seal groove and O-Ring from Face-Ø.
 *NOTE: Tee Branch has Bolt-Head recesses on Face 1.

BOLT-HEAD RECESS-TEE, BRANCH

NOMINAL PATTERN SIZE	H	L	W	W/2	K TB, RC, RT	O-RING SIZE NO.	TB, RT, RC CLAMP FACE BOLT KITS (2 BOLTS)
U26102	.62	1.00	1.25	.37	.44	010	IBK-SH2008-32x0.62
U26104	.75	1.25	1.50	.50	.56	011	IBK-SH2010-24x0.87
U26106	.87	1.50	2.00	.62	.62	014	IBK-SH2025-20x1.00
U26108	1.31	2.12	2.50	1.00	1.00	210	IBK-SH2031-18x1.50
U26112	1.62	2.56	3.00	1.12	1.25	214	IBK-SH2038-16x1.75
U26116	1.87	2.75	3.12	1.38	1.50	219	IBK-SH2038-16x2.00
U26120	2.12	3.12	3.50	1.66	1.69	222	IBK-SH2044-14x2.50
U26124	2.50	3.69	4.00	1.94	2.00	225	IBK-SH2050-13x2.75
U26132	3.00	4.00	4.37	2.44	2.50	228	IBK-SH2050-13x3.25

DESIGN C
 U61 2-BOLT FLANGE PORT MOUNTING SURFACE ON ALL FACES SPECIFIED. TAPPED HOLES WITHOUT O-RING GROOVE.



GAUGE and TEST PORT AVAILABILITY

AVAILABLE GAUGE and PORT LOCATIONS ARE THE SAME AS THOSE FOR THE CODE U61 4-BOLT MODULAR CONNECTORS (see page 20).

<p>Inserta Products, Inc. Blue Bell, Pa. 19422</p>	<p>MODULAR CONNECTORS UNIFIED CODE U61 2-BOLT FLANGE TYPE</p>	
--------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------	--